



NOTES:

1. THIS IS A ULTRA- HIGH VACUUM COMPONENT (UHV)
2. WHEN MACHINING VACUUM PARTS, USE SILICONE AND SULPHUR-BASED CUTTING FLUIDS IS PROHIBITED. USE ONE OF THE FOLLOWING:
A) CIMCOOL 5 STAR 49
B) TRIM SOL
3. THIS IS A UHV PART. THE PART MUST GO THROUGH A MULTIPLE STEP CLEANING PROCESS INVOLVING DEGREASING, WASHING AND DRY NITROGEN BLOWDOWN.
4. KEEP THE PART CLEAN AND WRAP FOR UHV PACKING WITH ALUMINUM FOIL.
5. DIMENSIONS IN [] ARE MILLIMETERS AND FOR REF. ONLY

REV	DATE	DESCRIPTION	BY	CHKD	DATE
1		INDIUM FOIL WAS SILVER FOIL	RAF	JC	10/8
1		ADDED .281 DIA. THRU	RAF	JC	10/8
1		15X Ø.277 WAS 16X Ø.12	RAF	JC	10/8

ITEM	QUANTITY	UNIT	DESCRIPTION	MATERIAL / SPEC	REV
PARTS LIST					
<p>THIS DRAWING IS THE PROPERTY OF ARGONNE NATIONAL LABORATORY</p> <p>A2416201</p> <p>Y3-30 MIRROR MOUNT ASSEMBLY FOR SRICAT 2-BM-A 1200mm MIRROR INDIUM FOIL</p>					
DESIGNER: R. KRAKORA DATE: 5/8/96		CHECKED: J. CHANG DATE: 6/18/96		DATE: 6/24/96 BY: T.M. KUZAY	
SURFACE FINISH: <input checked="" type="checkbox"/>		MATERIAL: INDIUM FOIL THICKNESS: .002 THK x 47.24 LG		SCALE: 1:2 PART: D	